

GODAVRI CEMENT PRIMER

Salient features:

- ❖ This primer is used on various surfaces like Plaster, brickwork, asbestos cement sheets, wood, metal, etc.
- ❖ This can be used as a Sealer Coat or Priming coat for any wall coating Or synthetic enamel..
- ❖ It has an excellent brushability, covering, alkali resistance, fungus resistance and sealing properties.

TECHNICAL DATA

Areas of application	:	Plastered walls, asbestos, brick work, concrete, wooden surfaces, etc.
Method of Application	:	Brush or conventional Spray
Consistency	:	Smooth & Uniform
Finish	:	Matt
Colour	:	Off White
Thinner Recommended	:	Godavri General Purpose Thinner
Application Viscosity	:	60-80 sec on FCB4 at 30 ⁰ C for brushing 25-30 sec on FCB4 at 30 ⁰ C for spraying
Drying at 30⁰C and 60 ± 5% r.h		
Surface Dry	:	2 Hrs.
Hard Dry	:	Overnight
Recoatibility	:	Excellent
Sandability	:	Smooth without paper clogging (after O/N drying).
Spreading Capacity	:	11±2 sq.mtrs./ltrs./coat depending upon surface and its preparation.
Flash Point	:	>30 ⁰ C
Keeping Properties	:	Not less than 6 months.

Rheological Properties	:	Material being thixotropic it has excellent flow & levelling. No Brush marks. No sagging
Packs Available	:	500 ml., 1 Ltr., 4 Ltrs., 20 Ltrs.

DIRECTION FOR USE :

Surface preparation :

Ensure that the surface is clean and free from any loose matter. Apply one or two coats if required. Allow 4 to 6 hrs. drying (depending upon climatic conditions) between 2 coats. To get best results light cut with emery paper no.280 and then apply subsequent paint.

TECHNICAL AID SERVICE PROVIDED ON REQUEST
--

Mfd. by : **GODAVRI PAINTS PVT. LTD.**

Tulsiram Gupta Mills Estate, Darukhana, Reay Road, Mumbai 400 010.

Tel.: 2372 3227 / 1249 , 2379 0135 Fax: 2377 5814

E-mail : admin@godavaripaints.com Website : www.godavaripaints.com

DEPOTS : AHMEDABAD, BHIWANDI, PUNE, VADODARA, BANGLORE

C & F / AGENTS : KANPUR, KOLHAPUR

DISCLAIMER FOR PRODUCTS :

The information presented in this publication, including technical data, details, pictures, illustrations, suggested procedures and suggested specifications, presented in this publication are for general information and representational purpose only. The information contained herein is subject to change without notice while every effort has been made to insure its accuracy, this information should not be used or relied upon for any specific application without independent professional examination and verification of its accuracy, suitability and applicability. The user shall be solely responsible for the selection, use, efficiency and suitability of the information, and anyone making use of the information does so at his own risk and assumes any and all liability resulting from such use. The information is provided on an "as is" basis and Godavri Paints Pvt. Ltd. disclaims any and all express or implied warranties of merchantability, fitness for any general or particular purpose or freedom from infringement of any patent, trademark, copyright, or proprietary right in regard to information or products contained or referred to herein. Nothing herein contained shall be construed as granting a license, express or implied under any patent, trademark, or copyright. In no event shall Godavri Paints Pvt. Ltd. be liable to user for any indirect, special, consequential or incidental damages arising out of the use, the results of use or inability to use the information.

The names of the products and trademarks are copyrights of Godavri Paints Pvt. Ltd. and its business partners who own the products developed by them that are marketed by Godavri Paints Pvt. Ltd.