

GODAVRI EXTERIOR PRIMER

Salient features:

- ❖ This product is based on Acrylic Binder and does not chalk and has good Properties.
- ❖ Needs no Curing.
- ❖ When used on exterior sand face plaster as primer gives good surface for application of top coats of Emulsion Paints.
- ❖ Cement Primer should not be kept exposed for a long period. It is recommended to overcoat it within 1 month time with appropriate paint.

TECHNICAL DATA

Areas of application	:	Exterior Cement Based Plasters.
Method of Application	:	Brush or Spray
Finish	:	Matt
Thinner	:	Potable water
Drying at 30°C and 60 ± 5% r.h		
Surface Dry	:	minimum 30 Minutes.
Hard Dry	:	minimum 5 Hours.
Spreading Capacity	:	Will vary from surface to surface. On Normal Sound Masonary Surface, it will give 9 to 12 sq.mtr./ltr./1 coat
Recommended thinning	:	70 to 80 % by volume with water
Recoating Interval	:	5 to 6 Hours
Packs Available	:	1 Ltr., 4 Ltrs., 20 Ltrs.

DIRECTION FOR USE :

Surface preparation :

Allow all new surfaces to dry out completely. Ensure that the surface is clean and free from grime, dust, flakes, grease, etc. For old, pre painted surfaces, remove all loosely adhering particles, powdery materials or defective paints by thorough brushing, scraping and water jetting, if required. For algae & fungus affected area, anti fungus wash is recommended.

Precaution :

It is recommended not to apply any kind of putty. Do not apply exterior acrylic primer during wet weather. On horizontal surfaces, it is recommended to do self priming of the topcoat material with additional coats of the same. For best results and for surfaces that remain powdery, friable or chalky after thorough preparation, application of topcoat material as primer with 1:1 dilution in water is recommended.

Application :

We recommend that this primer has to be applied on Dry Surface.

TECHNICAL AID SERVICE PROVIDED ON REQUEST
--

Mfd. by : **GODAVRI PAINTS PVT. LTD.**

Tulsiram Gupta Mills Estate, Darukhana, Reay Road, Mumbai 400 010.

Tel.: 2372 3227 / 1249, 2379 0135 Fax: 2377 5814

E-mail : admin@godavaripaints.com Website : www.godavaripaints.com

DEPOTS : AHMEDABAD, BHIWANDI, PUNE, VADODARA, BANGLORE

C & F / AGENTS : KANPUR, KOLHAPUR

DISCLAIMER FOR PRODUCTS :

The information presented in this publication, including technical data, details, pictures, illustrations, suggested procedures and suggested specifications, presented in this publication are for general information and representational purpose only. The information contained herein is subject to change without notice while every effort has been made to insure its accuracy, this information should not be used or relied upon for any specific application without independent professional examination and verification of its accuracy, suitability and applicability. The user shall be solely responsible for the selection, use, efficiency and suitability of the information, and anyone making use of the information does so at his own risk and assumes any and all liability resulting from such use. The information is provided on an "as is" basis and Godavri Paints Pvt. Ltd. disclaims any and all express or implied warranties of merchantability, fitness for any general or particular purpose or freedom from infringement of any patent, trademark, copyright, or proprietary right in regard to information or products contained or referred to herein. Nothing herein contained shall be construed as granting a license, express or implied under any patent, trademark, or copyright. In no event shall Godavri Paints Pvt. Ltd. be liable to user for any indirect, special, consequential or incidental damages arising out of the use, the results of use or inability to use the information.

The names of the products and trademarks are copyrights of Godavri Paints Pvt. Ltd. and its business partners who own the products developed by them that are marketed by Godavri Paints Pvt. Ltd.