

GODAVRI SATIN FINISH

SALIENT FEATURES :

- ❖ The product which develops characteristic texture when rolled over has also excellent flow leveling drying and durability.
- ❖ Dust pick-up being minimum, the film is easy to clean and retains fresh look for longer period.

TECHNICAL DATA

Areas of Application	:	Plaster, Wood, Metal and other such Interior surfaces.
Method of Application	:	Brush or Roller
Viscosity	:	120±10 sec. on Fordcup B4 at 30°C.
Thinner recommended	:	Godavri general purpose Thinner.
Application Viscosity	:	60±5 seconds on FCB4 at 30°C.
* Covering Capacity	:	15±3 sq.mtr./Litre/coat depending upon the substrate and temperature.
Drying at 30°C and 60% r.h		
Surface Dry	:	Less than 3 hrs.
Hard Dry	:	Overnight.
Finish	:	Typical texture with Lustre.

SURFACE PREPARATION :

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease, wax, etc. All surfaces should be thoroughly rubbed down using suitable abrasive paper and dusted off. New or bare surfaces should be primed with an appropriate primer.

DIRECTIONS FOR USE :

Apply Godavri Cement Primer (Solvent Base). Allow to dry overnight then apply conventional wall putty prepared using Godavri Putty Enamel to fill and level the undulation of the wall. Sand the surface after 6 to 8 Hrs. using emery paper No.180 and wipe clean. Apply second coat of Godavri Cement Primer (Solvent Base). Sand with emery paper no.320 after 6 to 8 Hrs. and wipe clean. Apply First coat of Godavri Satin Finish thinned with 10% by volume of Godavri General Purpose Thinner. Apply second coat of Godavri Satin Finish after 8 to 10 Hrs. using 10 to 15 % by volume of Godavri General Purpose Thinner.

TECHNICAL AID SERVICE PROVIDED ON REQUEST

Mfd. by : **GODAVRI PAINTS PVT. LTD.**

Tulsiram Gupta Mills Estate, Darukhana, Reay Road, Mumbai 400 010.

Tel.: 2372 3227 / 1249 . 2379 0135 Fax: 2377 5814

E-mail : admin@godavaripaints.com Website : www.godavaripaints.com

DEPOTS : AHMEDABAD, BHIWANDI, PUNE, VADODARA, BANGLORE

C & F / AGENTS : KANPUR, KOLHAPUR

DISCLAIMER FOR PRODUCTS :

The information presented in this publication, including technical data, details, pictures, illustrations, suggested procedures and suggested specifications, presented in this publication are for general information and representational purpose only. The information contained herein is subject to change without notice while every effort has been made to insure its accuracy, this information should not be used or relied upon for any specific application without independent professional examination and verification of its accuracy, suitability and applicability. The user shall be solely responsible for the selection, use, efficiency and suitability of the information, and anyone making use of the information does so at his own risk and assumes any and all liability resulting from such use. The information is provided on an "as is" basis and Godavri Paints Pvt. Ltd. disclaims any and all express or implied warranties of merchantability, fitness for any general or particular purpose or freedom from infringement of any patent, trademark, copyright, or proprietary right in regard to information or products contained or referred to herein. Nothing herein contained shall be construed as granting a license, express or implied under any patent, trademark, or copyright. In no event shall Godavri Paints Pvt. Ltd. be liable to user for any indirect, special, consequential or incidental damages arising out of the use, the results of use or inability to use the information.

The names of the products and trademarks are copyrights of Godavri Paints Pvt. Ltd. and its business partners who own the products developed by them that are marketed by Godavri Paints Pvt. Ltd.