

"PEARL – MAX "

ACRYLIC LATEX PAINT

Salient features:

- ❖ This product is an elastic, super protective & especially formulated for exterior walls. Due to its unique water resistant property and special paint preservatives it protects exterior walls from dampness, algae and fungus caused by lashing rain.

TECHNICAL DATA

Areas of application	:	Masonry, Concrete, Brickwork, etc.
Method of Application	:	Brush, Roller
Finish	:	Smooth with slight sheen
Thinner	:	Potable Water
Drying at 30°C and 60 ± 5% r.h		
Surface Dry	:	1 Hour
Hard Dry	:	4 to 6 Hours
Spreading Capacity (at recommended thinning)	:	On Normal Masonary surface by brushing : 5 – 6 sq.mtrs./ltr/2 coats
Recommended thinning	:	35 to 45% by volume with water
Recoating Interval	:	4 to 6 Hours
Packs Available	:	1 Ltr., 4 Ltrs., 20 Ltrs.

DIRECTION FOR USE :

APPLICATION :

Ensure that the plaster is completely dry, thoroughly clean and free from any grime, dust, flakes, grease, etc. Ensure that all water leakages/seepages are repaired before painting. For Old, prepainted surfaces, remove all loosely adhering particles, powdery material or defective paint by thorough brushing, scraping and water jetting, if required.

For areas severely affected by algae & fungus, application of **GODAVRI BIO WASH** is recommended.

Do not apply any kind of putty or primer. Surface imperfections such as holes, dents or cracks are to be filled with cement and sand mixture in the ration 1:3.

For best performance, it is recommended to apply one self priming coat of **PEARL – MAX ACRYLIC LATEX PAINT** after diluting 1 litre of paint with 1 litre of water, for any kind of surface or **COLORSOL** polymer Primer.

TECHNICAL AID SERVICE PROVIDED ON REQUEST

Mfd. by : **GODAVRI PAINTS PVT. LTD.**

Tulsiram Gupta Mills Estate, Darukhana, Reay Road, Mumbai 400 010.

Tel.: 2372 3227 / 1249 . 2379 0135 Fax: 2377 5814

E-mail : admin@godavaripaints.com Website : www.godavaripaints.com

DEPOTS : AHMEDABAD, BHIWANDI, PUNE, VADODARA, BANGLORE

C & F / AGENTS : KANPUR, KOLHAPUR

DISCLAIMER FOR PRODUCTS :

The information presented in this publication, including technical data, details, pictures, illustrations, suggested procedures and suggested specifications, presented in this publication are for general information and representational purpose only. The information contained herein is subject to change without notice while every effort has been made to insure its accuracy, this information should not be used or relied upon for any specific application without independent professional examination and verification of its accuracy, suitability and applicability. The user shall be solely responsible for the selection, use, efficiency and suitability of the information, and anyone making use of the information does so at his own risk and assumes any and all liability resulting from such use. The information is provided on an "as is" basis and Godavri Paints Pvt. Ltd. disclaims any and all express or implied warranties of merchantability, fitness for any general or particular purpose or freedom from infringement of any patent, trademark, copyright, or proprietary right in regard to information or products contained or referred to herein. Nothing herein contained shall be construed as granting a license, express or implied under any patent, trademark, or copyright. In no event shall Godavri Paints Pvt. Ltd. be liable to user for any indirect, special, consequential or incidental damages arising out of the use, the results of use or inability to use the information.

The names of the products and trademarks are copyrights of Godavri Paints Pvt. Ltd. and its business partners who own the products developed by them that are marketed by Godavri Paints Pvt. Ltd.