


*Coloring Excellence -
Providing Total Paint Solutions*

GODAVRI
PAINTS

GODAVRI ACRYLIC DISTEMPER

Godavri Paint's Acrylic Distemper is a smooth water based interior grade paint modified with co-polymer acrylic binders and other performance additives to give the wall a smooth matt look which is durable, fungus free and has good color retention.



TECHNICAL DATA

Area Of Application	Masonry walls, Fiber board, RCC, Putty surfaces
Method Of Application	Brush, Roller, Spray
Consistency	Smooth Paste like
Finish	Matt
Recommended Thinner	Potable Water
Viscosity	160+10 units On Ford Cup
Drying Time	Surface dry: 15 minutes Hard Dry: Minimum 4 Hours
Coverage	4 sqmtr - 5 sqmtr in 2 coats / Kg *Actual coverage may vary to the quoted coverage due to factors like skill, surface porosity, tools, site conditions etc *
Dilution by Volume	40% to 50%
Film Thickness	70 - 80 microns in 2 coats
Packing	20 kg, 5 kg, 1 kg

PRODUCT APPLICATION

SURFACE PREPARATION

Washing - Clean the surface which has to be painted with dry muslin cloth and make sure that the surface is free from all loose particles and foreign dusts settled on the walls.

Surface imperfections - If any like cracks, holes, loose plaster etc should be repaired using white cement and fine sand in proper proportion to stop leakage or seepage in future, prior to application of putty.

Precautions - If the surface has continuous seepage or dampness do not apply the product.

APPLICATION

- Stir the content thoroughly before opening the lid
- Dilute the material as stated in the technical data
- Apply 2-3 coats of Godavri Acrylic Putty for best result
- Apply 1st coat of Godavri Interior Primer after sanding
- Roller / Brush Apply 1st Coat of Acrylic Distemper
- Roller / Brush Apply 2nd Coat of Acrylic Distemper
- Apply 3rd coat for best results (Optional)



SAFETY FEATURES

- ✓ Store the container with the lid tightly closed in an upright position, in a cool, dry place
- ✓ Keep out of reach of children and away from food, drink
- ✓ May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- ✓ Wear eye protection during application.
- ✓ In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of skin contact immediately wash skin with soap and plenty of water.
- ✓ Get medical attention if irritation develops or persists.
- ✓ Do not breathe vapour or spray.
- ✓ It is recommended to wear suitable nose pad during sanding and surface preparation to avoid -dust inhalation
- ✓ Do not pour leftover paint down the drain or in water courses.
- ✓ In the event of spills, contain spillage using sand or earth.
- ✓ No added Lead, Mercury or Chromium compounds

TECHNICAL AID SERVICE PROVIDED ON REQUEST



Manufactured by

GODAVRI PAINTS PVT. LTD.

Admin Office: Tulsiram Gupta Mills Estate,
Darukhana, Reay Road, Mumbai 400010

For Customer Care contact: 022 23721249

admin@godavaripaints.com
www.godavaripaints.com