


*Coloring Excellence -
Providing Total Paint Solutions*

GODAVRI
PAINTS

KLASSIC

Exterior Emulsion Paint

Godavri Paint's Klassic is a smooth water based exterior grade paint modified with flexible co polymer acrylic modified binders and other performance additives to give the wall a new look which is suitable for moderate humid climate along with resistance to algae growth, black spots caused on the surface due to lashing rains.



TECHNICAL DATA

Area Of Application	Masonry walls, Fiber board, RCC
Method Of Application	Brush, Roller, Spray
Consistency	Smooth
Finish	Low sheen
Recommended Thinner	Potable Water
Viscosity	110+10 KU
Drying Time	Surface dry: 30 minutes Hard Dry: Minimum 4 Hours
Coverage	5 sqmtr - 6 sqmtr per Ltr / 2 coats *Actual coverage may vary to the quoted coverage due to factors like skill, surface porosity, tools, site conditions etc*
Dilution by Volume	40% to 50%
Film Thickness	90-100 microns in 2 coats
Packing	20 ltr, 4 ltr, 1 ltr

PRODUCT APPLICATION

SURFACE PREPARATION

Washing - Clean the surface which has to be painted with coir brush and water and ensure that it is free from any loose paint dust, grease and growth of algae, fungus or moth.

Surface imperfections - If any like cracks, holes, loose plaster etc should be repaired using white cement and fine sand in proper proportion to stop leakage or seepage in future.

Precautions - Do not apply the product if surface is subjected to continuous dampness / Seepage even after due surface preparation.

APPLICATION

- Stir the content thoroughly before opening the lid
- Dilute the material as stated in the technical data
- Apply 1st coat of Godavri Exterior Primer (Optional)
- Roller / Brush Apply 1st Coat of Klassic
- Roller / Brush Apply 2nd Coat of Klassic
- Horizontal Surface may require 3rd coat for protection



SAFETY FEATURES

- ✓ Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- ✓ Keep out of reach of children and away from food, drink.
- ✓ May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- ✓ Wear eye protection during application.
- ✓ In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of skin contact immediately wash skin with soap and plenty of water.
- ✓ Get medical attention if irritation develops or persists.
- ✓ Do not breathe vapour or spray.
- ✓ It is recommended to wear suitable nose pad during sanding and surface preparation to avoid-dust inhalation.
- ✓ Do not pour leftover paint down the drain or in water courses.
- ✓ In the event of spills, contain spillage using sand or earth.
- ✓ No added Lead, Mercury or Chromium compounds.

TECHNICAL AID SERVICE PROVIDED ON REQUEST



Manufactured by

GODAVRI PAINTS PVT. LTD.

Admin Office: Tulsiram Gupta Mills Estate,
Darukhana, Reay Road, Mumbai 400010

For Customer Care contact: 022 23721249

admin@godavaripaints.com
www.godavaripaints.com