

*Coloring Excellence -
Providing Total Paint Solutions*

GODAVRI
PAINTS

PEARL LONGLIFE

-Anti Carbonation Paint

Godavri Paint's "PEARL LONGLIFE" Anti Carbonation Coating is a Polymer Waterbased flexible protective coating for exposed concrete and cementitious surfaces. Ideal for use as an anti-carbonation coating to protect exposed reinforced concrete surfaces of bridges, tunnels, etc.



TECHNICAL DATA

Area of Application:	Masonry walls, Fiber boards, RCC
Method of Application:	Brush, Roller, Spray
Consistency:	Smooth
Finish:	Medium Sheen
Recommended Thinner:	Potable Water
Viscosity:	120 +/- 10 KU
Drying Time:	Surface Dry: 30 minutes Hard Dry: Minimum 4 Hours
Solid Content:	70 +/- 3 %
Coverage:	6-7 sqmtr / ltr in 2 coats *Actual coverage may vary to the quoted coverage due to factors like skill, surface porosity, tools, Site conditions etc.
Dilution:	20%-30% Maximum
Dry Film Thickness:	80-100 microns in 2 coats For 150 microns DFT the coverage will be 3-4 sqmtr/ltr in 2 or more coats
Packing:	20 Ltr

PRODUCT APPLICATION

SURFACE PREPARATION

Washing - Clean the surface which has to be painted with coir brush and water and ensure that it is free from any loose paint dust, grease and growth of algae, fungus or moth.

Surface imperfections - If any like cracks, holes, loose plaster etc should be repaired using white cement and fine sand in proper proportion to stop leakage or seepage in future.

Precautions - Do not apply the product if surface is subjected to continuous dampness / Seepage even after due surface preparation.

APPLICATION

- Stir the content thoroughly before opening the Lid
- Dilute the material as stated in the Technical Data
- Apply 1 coat of Appropriate Primer as per requirement
- Roller / Brush / Spray apply 1st Coat of Pearl Longlife
- Roller / Brush / Spray apply 2nd Coat of Pearl Longlife
- Roller / Brush / Spray apply additional coats for required DFT



SAFETY FEATURES

- ✓ Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- ✓ Keep out of reach of children and away from food, drink.
- ✓ May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- ✓ Wear eye protection during application.
- ✓ In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of skin contact immediately wash skin with soap and plenty of water.
- ✓ Get medical attention if irritation develops or persists.
- ✓ Do not breathe vapour or spray.
- ✓ It is recommended to wear suitable nose pad during sanding and surface preparation to avoid-dust inhalation.
- ✓ Do not pour leftover paint down the drain or in water courses.
- ✓ In the event of spills, contain spillage using sand or earth.
- ✓ No added Lead, Mercury or Chromium compounds.

TECHNICAL AID SERVICE PROVIDED ON REQUEST



Manufactured by

GODAVRI PAINTS PVT. LTD.

Admin Office: Tulsiram Gupta Mills Estate,
Darukhana, Reay Road, Mumbai 400010

For Customer Care contact: 022 23721249

admin@godavaripaints.com
www.godavaripaints.com