

*Coloring Excellence -
Providing Total Paint Solutions*

GODAVRI
PAINTS

SUPREME

White Cement Based Putty

SUPREME white cement based putty is water resistant for concrete / mortar walls and ceilings. 'Supreme' can be applied even on moist surfaces (Internal/External). 'Supreme' has more adhesive strength, durability and increases the life of paints. 'Supreme' though white cement based, does not require water curing but as the conditions of the surfaces differ and ambient temperatures differ, it is preferable that after application of Supreme Putty, next day it should be cured as a precautionary measure. It renders a smooth and durable surface suitable for all kinds of paints.

Application Procedure:

Surface preparation

Remove all the loosely adhering material from the wall surface with the help of emery stone, putty blade or wire brush. Moisten the wall with sufficient quantity of clean water.

Mixing of 'Supreme'

Mix Supreme putty with 35-40% clean water slowly to make a paste. Continue the mixing of material for 10-15 minutes till a uniform paste is formed.

Application on surface

Apply first coat of 'Supreme' uniformly on already moistened surface with the help of putty blade or trowel. Allow the surface to dry for at least three hours and then apply a second coat of putty. Leave the surface to dry completely. Always prepare the required quantity of 'Supreme' putty. And use it within three hours of mixing with water. The total thickness of both the coats should be limited to a maximum of 1.5 mm. After complete drying of the surface, if needed, the surface should be rubbed with fine waterproof emery paper. The surface is now ready for painting.

Precautions while using

Though it contains only non-toxic material still care should be taken

to avoid dust inhalation while mixing and handling. In case of contact with eyes or mouth, wash with plenty of water. Keep it in a dry place and out of reach of children.

Storage

'Supreme' should be stored in a dry place.

Packing

'Supreme' is available in 40kg & 20kg packs.

Technical data

Property	
Tensile Adhesion Strength at 28 days	2.26 N / mm ²
Compressive Strength at 28 days	13.46 N/mm ²
Pot life	2-3 hrs
Water Demand	35-40%
Surface hardness	3.0 N
Maximum thickness of the total coats	1.5mm
Coverage on smooth surface	10-15 sqft/kg in 2 coats

TECHNICAL AID SERVICE PROVIDED ON REQUEST



Manufactured by

GODAVRI PAINTS PVT. LTD.

Admin Office: Tulsiram Gupta Mills Estate,
Darukhana, Reay Road, Mumbai 400010

For Customer Care contact: 022 23721249

admin@godavaripaints.com
www.godavaripaints.com