

*Coloring Excellence -
Providing Total Paint Solutions*

GODAVRI
PAINTS

SUPREME PLUS

Waterproofing Cement Putty

Supreme Plus Waterproofing Cement Putty is white cement based highly polymerized flexible grade of external surfaces levelling & finishing product to provide very durable base for painting.

Supreme Plus has more adhesive strength, durability and increases the life of paints. Supreme plus though white cement based, does not require water curing. It renders smooth and durable surface suitable for all kinds of paints.

Provides high adhesion with concrete surfaces.

The applied coating will resist water penetration into wall & protect concrete & other surfaces. The product can be applied with 1mm to 2mm thickness in one coat to cover undulations

Application Procedure:

Surface preparation

Remove all the loosely adhering material from the wall surface with the help of emery stone, putty blade or wire brush. Moisten the wall with sufficient quantity of clean water.

Mixing of 'Supreme'

Mix Supreme putty with 35-40% clean water slowly to make a paste. Continue the mixing of material for 10-15 minutes till a uniform paste is formed.

Application on surface

Apply first coat of 'Supreme' uniformly on already moistened surface with the help of putty blade or trowel. Allow the surface to dry for at least three hours and then apply a second coat of putty. Leave the surface to dry completely. Always prepare the required quantity of 'Supreme' putty. And use it within three hours of mixing with water. The total thickness of both the coats should be limited to a maximum of 1.5 mm. After complete drying of the surface, if needed, the surface should be rubbed with fine waterproof emery paper. The surface is now ready for painting.

Precautions while using

Though it contains only non-toxic material still care should be taken to avoid dust inhalation while mixing and handling. In case of contact with eyes or mouth, wash with plenty of water. Keep it in a dry place and out of reach of children.

Shelf Life :

6 months

Storage

'Supreme' should be stored in a dry place.

Packing

'Supreme' is available in 40kg pack.

Technical data

Property	
Appearance	Free flowing White Powder
Tensile Adhesion Strength (Pull off Strength)	Min. 0.8 Mpa
Compressive Strength at 28 days	> 7 Mpa
Pot life	2-3 hrs
Water Demand	30% (Approx)
Residue on 240 mesh	< 3%
Water Penetration /Absorption by Karsten tube	< 1.0 ml (6 hours @ 30° C
Maximum thickness	1.5mm
Coverage on smooth surface	10-15 sqft/kg in 1 coat

TECHNICAL AID SERVICE PROVIDED ON REQUEST



•Manufactured by

GODAVRI PAINTS PVT. LTD.

Admin Office: Tulsiram Gupta Mills Estate,
Darukhana, Reay Road, Mumbai 400010
For Customer Care contact: 9136499404,
9136499407, 9136499410

admingodavaripaints.com
www.godavaripaints.com