

*Coloring Excellence -  
Providing Total Paint Solutions*

**GODAVRI**  
PAINTS

## GODAVRI SEMI GLOSS AQUANAMEL

Godavri Paint's Semigloss Aquanamel is a superior water based interior / exterior grade enamel. When applied it gives a rich satin look to the walls and provides a tough and a durable film over the substrate. Modified with Super high quality acrylic binders and other performance additives it gives the wall a good stain resistance, smooth high sheen rich look which is durable, fungus free and has a good color retention with non yellowing properties.



## TECHNICAL DATA

|                       |                                                                                                                                                                                   |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Area Of Application   | Masonry walls, Fiber board, RCC, Putty surfaces                                                                                                                                   |
| Method Of Application | Brush, Roller, Spray                                                                                                                                                              |
| Consistency           | Smooth                                                                                                                                                                            |
| Finish                | High Sheen                                                                                                                                                                        |
| Recommended Thinner   | Potable Water                                                                                                                                                                     |
| Viscosity             | 120+10 KU                                                                                                                                                                         |
| Drying Time           | Surface dry: 30 minutes<br>Hard Dry: Minimum 4 Hours                                                                                                                              |
| Coverage              | 10 sqmtr - 12 sqmtr in 2 coats / Ltr<br><small>*Actual coverage may vary to the quoted coverage due to factors like skill, surface porosity, tools, site conditions etc *</small> |
| Dilution by Volume    | 30% to 40%                                                                                                                                                                        |
| Film Thickness        | 80 - 90 microns in 2 coats                                                                                                                                                        |
| Packing               | 20 ltr, 4ltr, 1 ltr                                                                                                                                                               |

## PRODUCT APPLICATION

### SURFACE PREPARATION

**Washing** - Clean the surface which has to be painted with dry muslin cloth and make sure that the surface is free from all loose particles and foreign dusts settled on the walls.

**Surface imperfections** - If any like cracks, holes, loose plaster etc should be repaired using white cement and fine sand in proper proportion to stop leakage or seepage in future prior to application of putty.

**Precautions** - If the surface has continuous seepage or dampness do not apply the product.

### APPLICATION

- Stir the content thoroughly before opening the lid
- Dilute the material as stated in the technical data
- Apply 2-3 Coats of Godavri Acrylic Putty for best finish
- Apply 1st coat of Godavri Interior Primer after sanding
- Roller / Brush Apply 1st Coat of Semi Gloss Aquanamel
- Roller / Brush Apply 2nd Coat of Semi Gloss Aquanamel
- Apply 3rd coat for best results (Optional)



## SAFETY FEATURES

- ✓ Store the container with the lid tightly closed in an upright position, in a cool, dry place
- ✓ Keep out of reach of children and away from food, drink
- ✓ May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- ✓ Wear eye protection during application.
- ✓ In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of skin contact immediately wash skin with soap and plenty of water.
- ✓ Get medical attention if irritation develops or persists.
- ✓ Do not breathe vapour or spray.
- ✓ It is recommended to wear suitable nose pad during sanding and surface preparation to avoid -dust inhalation
- ✓ Do not pour leftover paint down the drain or in water courses.
- ✓ In the event of spills, contain spillage using sand or earth.
- ✓ No added Lead, Mercury or Chromium compounds

TECHNICAL AID SERVICE PROVIDED ON REQUEST



Manufactured by

**GODAVRI PAINTS PVT. LTD.**

Admin Office: Tulsiram Gupta Mills Estate,  
Darukhana, Reay Road, Mumbai 400010

For Customer Care contact: 022 23721249

admin@godavaripaints.com  
www.godavaripaints.com