Coloring Excellence – Providing Total Paint Solutions



PEARL ULTIMA Advanced Weatherproof Paint

Godavri Paint's PEARL ULTIMA is a smooth water based high performance exterior grade paint modified with top of the line acrylic modified binders and other performance additives to give the wall a rich look along with a special feature of low dust pick up and cleaning properties.





TECHNICAL DATA

Area Of Application Masonary walls, Fiber board, RCC

Method Of Application Brush, Roller, Spray

Consistency Smooth

Finish High sheen

Recommended Thinner Potable Water

Viscosity 130+10 KU

Drying Time Surface dry: 30 minutes

Hard Dry: Minimum 4 Hours

Coverage 5-6 sqmtr per Lit / 2 coats

*Actual coverage may vary to the quoted coverage due to factors like skill, surface porosity, tools, site conditions etc *

Dilution by Volume 40% to 50%

Film Thickness 90-100 microns in 2 coats

Packing 20 ltr, 4 ltr, 1 ltr

PRODUCT APPLICATION

SURFACE PREPARATION

Washing - Clean the surface which has to be painted with coir brush and water and ensure that it is free from any loose paint dust, grease and growth of algae, fungus or moth.

Surface imperfections - If any like cracks, holes, loose plaster etc should be repaired using white cement and fine sand in proper proportion to stop leakage or seepage in future.

Precautions - Do not apply the product if surface is subjected to continuous dampness / Seepage even after due surface preparation.

APPLICATION

- Stir the content thoroughly before opening the lid
- Dilute the material as stated in the technical data
- Apply 1st coat of Godavri Exterior Primer
- Roller / Brush Apply 1st Coat of Pearl Ultima
- Roller / Brush Apply 2nd Coat of Pearl Ultima
- Horizontal Surface may require 3rd coat for protection



SAFETY FEATURES

- ✓ Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from food, drink.
- ✓ May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application.
- ✓ In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of skin contact immediately wash skin with soap and plenty of water.
- Get medical attention if irritation develops or persists.
- ✓ Do not breathe vapour or spray.
- ✓ It is recommended to wear suitable nose pad during sanding and surface preparation to avoid-dust inhalation.
- ✓ Do not pour leftover paint down the drain or in water courses.
- ✓ In the event of spills, contain spillage using sand or earth.
- ✓ No added Lead, Mercury or Chromium compounds.

TECHNICAL AID SERVICE PROVIDED ON REQUEST





Manufactured by

GODAVRI PAINTS PVT. LTD.

Admin Office: Tulsiram Gupta Mills Estate, Darukhana, Reay Road, Mumbai 400010

For Customer Care contact: 022 23721249

admin@godavaripaints.com www.godavaripaints.com