ayant

CEMPRIMER ADHESIVE LIQUID FOR CEMENT

CEMPRIMER is a white colour based on polymers. It has excellent adhesive property. It is used as a Primer for SUPREMCEM to improve adhesiveness on difficult surfaces such as

- RCC surfaces a.
- Smooth non-absorbent Cement surfaces b.
- C. Old surfaces
- d. Surfaces where lime wash or distempers have been used earlier and now SUPREMCEM has to be applied.

Surface Preparation:

Before applying CEMPRIMER surface preparation is necessary. The surface has to be scraped properly so that friable matters and foreign/loose particles are cleared off the surface.

Mixing:

CEMPRIMER is mixed with clean drinking water in equal proportion and stirred thoroughly to give a homogenous solution ready for application.

Application:

CEMPRIMER is used as a primer coat, is scrubbed vigorously into the surface. SUPREMCEM is applied after a minimum interval of 8 to 10 hours. For application procedure of SUPREMCEM you may refer to literature on SUPREMCEM.

Covering Capacity:

SURFACE	Sq. Metres / per litro
1. Cement/Sand Rendering smooth	15
2. Cement/Sand Rendering wood float finish	12.5
3. Distempers / Lime Wash	13.5
4. Old SUPREMCEM Surfaces	12.5
5. Brick Work	2.65

CEMPRIMER as a key coat for plastering unhacked concrete:

Mixing Procedure:

First CEMPRIMER is diluted with equal measure of water. Then it is added to 2 volumes of portland cement and 3 volumes of fine; clean sand which will provide a thick slurry ready for application.

Application:

The unhacked concrete surface to be treated with **CEMPRIMER** slurry has to be free from moisture. The **CEMPRIMER** slurry is applied by brushing vigorously into the surface and immediately stipped with full barrister brush in order to form a close textured key coat. This key coat has to be kept for minimum one week depending on the weather.

Now the key coat is ready to take on 2 coats of normal plaster.

Packing: In 20 Litre Drum, 5 Litre Cans

TECHNICAL AID SERVICE PROVIDED ON REQUEST

Mfd by JAYANT COLR & CHEMICAL INDS.

Tulsiram Gupta Mills Estate, Darukhana, Reay Road, Mumbai 400 010.

Tel.: 2372 3227 / 1249 . 2379 0135 Fax: 2377 5814 E-mail: admin@jayantcolor.com / admin@godavaripaints.com

Website: www.jayantcolor.com / www.godavaripaints.com

DEPOTS: AHMEDABAD, BHIWANDI, PUNE, VADODARA, BANGLORE

C & F / AGENTS : KANPUR, KOLHAPUR

DISCLAIMER FOR PRODUCTS:

The information presented in this publication, including technical data, details, pictures, illustrations, suggested procedures and suggested specifications, presented in this publication are for general information and representational purpose only. The information contained herein is subject to change without notice while every effort has been made to insure its accuracy, this information should not be used or relied upon for any specific application without independent professional examination and verification of its accuracy, suitability and applicability. The user shall be solely responsible for the selection, use, efficiency and suitability of the information, and anyone making use of the information does so at his own risk and assumes any and all liability resulting from such use. The information is provided on an "as is" basis and Jayant Color & Chemical Industries disclaims any and all express or implied warranties of merchantability, fitness for any general or particular purpose or freedom from infringement of any patent, trademark, coparight, or proprietary right in regard to information or products contained or referred to herein. Nothing herein contained shall be construed as granting a license, express or implied under any patent, trademark, or copyright. In no event shall Jayant Color & Chemical Industries be liable to user for any indirect, special, consequential or incidental damages arising out of the use, the results of use or inability to use the information.

The names of the products and trademarks are copyrights of Jayant Color & Chemical Industries and its business partners who own the products developed by them that are marketed by Jayant Color & Chemical Industries.