

*Coloring Excellence -  
Providing Total Paint Solutions*

**GODAVRI**  
PAINTS

# GODAVRI BIO WASH

Godavri Paint's Biowash is an aqueous solution with fungicide and algacide to resist and kill the fungus growth on the surface before painting the affected surface.



## TECHNICAL DATA

Area Of Application	Masonry walls, Fiber board, RCC, Pre painted buildings
Method Of Application	Brush , Roller
Consistency	Liquid
Finish	Clear
Recommended Thinner	N.A.
Viscosity	40+10 KU
Drying Time	Surface dry: 1 hours Hard Dry: Minimum 8 Hours
Coverage	8 sqmtr - 9 sqmtr in 1 coats *Actual coverage may vary to the quoted coverage due to factors like skill, surface porosity, tools, site conditions etc *
Dilution by Volume	Ready to use
Film Thickness	30-40 microns in 1 coats
Packing	20 ltr

## PRODUCT APPLICATION

### SURFACE PREPARATION

**Washing** - Clean the surface which has to be painted with coir brush and water and ensure tha it is free from any loose paint dust, grease and growth of algae, fungus or moth.

**Surface imperfections** - If any like cracks, holes, loose plaster etc should be repaired using white cement and fine sand in proper proportion to stop leakage or seepage in future.

**Precautions** - Do not apply the product if surface is subjected to continuous dampness / Seepage even after due surface preparation.

### APPLICATION

- Stir the content thoroughly before opening the lid
- Dilute the material as stated in the technical data
- Apply 1 coat of Bio wash on the fungus affected area
- Scrub the applied area with water and coir brush
- Apply 2 -3 Coats of Exterior Paint for best results



## SAFETY FEATURES

- ✓ Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- ✓ Keep out of reach of children and away from food, drink.
- ✓ May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- ✓ Wear eye protection during application.
- ✓ In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of skin contact immediately wash skin with soap and plenty of water.
- ✓ Get medical attention if irritation develops or persists.
- ✓ Do not breathe vapour or spray.
- ✓ It is recommended to wear suitable nose pad during sanding and surface preparation to avoid-dust inhalation.
- ✓ Do not pour leftover paint down the drain or in water courses.
- ✓ In the event of spills, contain spillage using sand or earth.
- ✓ No added Lead, Mercury or Chromium compounds.

TECHNICAL AID SERVICE PROVIDED ON REQUEST



Manufactured by

**GODAVRI PAINTS PVT. LTD.**

Admin Office: Tulsiram Gupta Mills Estate,  
Darukhana, Reay Road, Mumbai 400010

For Customer Care contact: 022 23721249

admin@godavaripaints.com

www.godavaripaints.com