

*Coloring Excellence -
Providing Total Paint Solutions*

GODAVRI
PAINTS

INSPIRA ELITE SPRAY TEXTURE

Inspira Elite Spray Finish provides unique alternative to traditional wall coatings with infinite number of colour combination for the Exteriors & Interiors. Inspira Elite Spray Finish is not only simply decorative and aesthetic but also highly durable, economical and can withstand harsh climatic conditions. Inspira Elite Spray Finish is formulated out of special grade of acrylic emulsions of siliceous aggregates. Inspira Elite Spray Finish can have numerous designs with different machines and application tools to provide best aesthetics to the walls.



TECHNICAL DATA

Area Of Application	Masonry walls, Fiber board, RCC
Method Of Application	Spray gun / Trowel if required
Consistency	Paste
Finish	Bubble
Recommended Thinner	Potable Water
Viscosity	300 to 400 units on penetrometer
Drying Time	Surface dry: 2 hours Hard Dry: Minimum 8 Hours
Coverage	4 sqft - 6 sqft per kg / 1 coats <small>*Actual coverage may vary to the quoted coverage due to factors like skill, surface porosity, tools, site conditions etc*</small>
Dilution by Volume	2% to 5%
Film Thickness	1mm to 1.5mm per coat depending on final design
Packing	25 Kg

PRODUCT APPLICATION

SURFACE PREPARATION

Washing - Clean the surface which has to be painted with coir brush and water and ensure that it is free from any loose paint dust, grease and growth of algae, fungus or moth.

Surface imperfections - If any like cracks, holes, loose plaster etc should be repaired using white cement and fine sand in proper proportion to stop leakage or seepage in future.

Precautions - Do not apply the product if surface is subjected to continuous dampness / Seepage even after due surface preparation

APPLICATION

- Stir the content thoroughly before opening the lid
- Dilute the material as stated in the technical data
- Apply 1st coat of Godavri Exterior Primer
- Apply 1 Coat of Inspira Elite texture with Spray Gun
- Apply 2-3 Coats of Desired Paint for best result



SAFETY FEATURES

- ✓ Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- ✓ Keep out of reach of children and away from food, drink.
- ✓ May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- ✓ Wear eye protection during application.
- ✓ In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of skin contact immediately wash skin with soap and plenty of water.
- ✓ Get medical attention if irritation develops or persists.
- ✓ Do not breathe vapour or spray.
- ✓ It is recommended to wear suitable nose pad during sanding and surface preparation to avoid-dust inhalation.
- ✓ Do not pour leftover paint down the drain or in water courses.
- ✓ In the event of spills, contain spillage using sand or earth.
- ✓ No added Lead, Mercury or Chromium compounds.

TECHNICAL AID SERVICE PROVIDED ON REQUEST



Manufactured by

GODAVRI PAINTS PVT. LTD.

Admin Office: Tulsiram Gupta Mills Estate,
Darukhana, Reay Road, Mumbai 400010

For Customer Care contact: 022 23721249

admin@godavaripaints.com

www.godavaripaints.com